



## 18oz Blackout

### Specifications

|                        |   |
|------------------------|---|
| Description:           | Vinyl laminated on a weft insertion scrim base of high tenacity filament polyester. |
| Weight:                | 18 oz. per lineal yard  |
| Width:                 | 37.5, 75  |
| Tensile Lb./In.        | W293 / F269   |
| Tear Lb.               | W112 / F113   |
| Hydrostatic (PSI):     | 423   |
| Surface:               | Matte   |
| Transparency:          | No  |
| Abrasion Resistance:   | Excellent   |
| Dimensional Stability: | Excellent   |
| Flexibility:           | Excellent in both hot and cold environments   |
| Flame Resistance:      | Yes   |
| Mildew Resistance:     | Excellent   |
| Chemical Resistance:   | Excellent   |
| Water Repellency:      | Excellent – Water Proof   |
| Oil Resistance:        | Excellent   |
| Sewability:            | Excellent   |
| Heat Sealability:      | Excellent. Can be sealed by hot air weg welder or radio frequency bar type.         |



HERCULITE®

P.O. Box 435, Emigsville, PA 17318 USA

717-764-1192

800-772-0036

Fax: 717-764-5211

[www.herculite.com](http://www.herculite.com)

EMAIL: [customercare@herculite.com](mailto:customercare@herculite.com)